

Multi Environment Corrosion Protection System

- **GUARDIAN Petrolatum Mastic HT** is a key component of the GUARDIAN Petrolatum System.
- **GUARDIAN Petrolatum Mastic HT** is a blended reinforced petrolatum. Incorporating inert fillers, GUARDIAN Petrolatum Mastic HT also contains corrosion inhibitors and thermal extenders.
- **GUARDIAN Petrolatum Mastic HT** is stable in nature and maintaining its plasticity over a wide temperature range.
- **GUARDIAN Petrolatum Mastic HT** profiles crevices and sharp angles enabling **GUARDIAN Petrolatum Tape ST & HT** to be applied without bridging or creating voiding.

PROPERTIES

Property	Test Method	Value
Flash Point	ASTM D92	180°C
Specific Gravity	ASTM D70 @ 25°C (Mod)	1.1 (Average)
Drop Melting Point	ASTM D127 (Mod)	75°C
Volume per block*		.003m3
*Note that the quantity of mastic required is applicator dependent.		
Application trials should be conducted where possible to determine requirements.		
Application Temperature	-10 to + 50°C	
Service Temperature	-10 to + 75°C	
Service Life	30 Years +	
Shelf Life	30 Years +	

PACKAGING

Part No.	Weight	Unit	Carton Qty
FG001255	3kg	Block	8 Blocks

APPLICATION

Refer to the GUARDIAN Petrolatum System: Application Data Sheet.

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.