

- **GUARDIAN MM Mastic** is a key component of the **GUARDIAN Systems**.
- **GUARDIAN MM Mastic** is Petrolatum Compound blended with inert fillers, thermal extenders, corrosion inhibitors and wide spectrum biocide.
- **GUARDIAN MM Mastic** is formulated for stability and plasticity over a wide temperature range.
- **GUARDIAN MM Mastic** is for use in filling voids and profiling sharp angular changes to enable tape application without bridging or voiding.

PROPERTIES

| Property | Test Method | Value |
|--------------------|-----------------------|---------------------|
| Flash Point | | 180°C |
| Specific Gravity | ASTM D70 @ 25°C (Mod) | 1.1 (Average) |
| Drop Melting Point | ASTM D127 (Mod) | 75°C |
| Volume per block* | | 0.003m ³ |

*Note that the quantity of mastic required is applicator dependent.

Confirmatory trials should be conducted where possible to determine requirements.

| | |
|--------------------------|--------------|
| Application Temperatures | -10 to +50°C |
| Service Temperature | -10 to +65°C |
| Service Life | 20 Years + |
| Shelf Life | 3 Years + |

PACKAGING

| Part No. | Weight | Unit | Carton Qty |
|----------|--------|-------|-----------------|
| MM03 | 3kg | Block | 8 Blocks/Carton |

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.

BENEFITS

Isolates marine pile from the environment
Salt and seawater resistant
Contains water repellent and displacing agents

APPLICATION

Refer to the relevant GUARDIAN System Application Data Sheet