

## Multi Environment Corrosion Protection System

- **GUARDIAN Petrolatum Mastic UL** is a key component of the GUARDIAN Petrolatum System.
- **GUARDIAN Petrolatum Mastic UL** is a reinforced petrolatum compound incorporating inert fillers, corrosion inhibitors and closed cell polymer beads, reducing product density.
- **GUARDIAN Petrolatum Mastic UL** is inert, being stable in nature and maintaining its plasticity over a wide temperature range.
- **GUARDIAN Petrolatum Mastic UL** profiles crevices and sharp angles, enabling **GUARDIAN Petrolatum Mastic UL** to be applied without bridging or voiding.

## PURPOSE

Protects against corrosion Above and Below Ground on Pipes and Pipe Fittings, Tie Rods, and Other Applications.

## PROPERTIES

Property	Test Method	Value
Specific Gravity	ASTM D70 @ 25°C (Mod)	0.35 ± 0.50
Drop Melting Point	ASTM D127 (Mod)	65°C
Application Temperature	-10 to + 50°C	
Service Temperature	-10 to + 55°C	
Shelf Life & service Life	30 Years +	

## PACKAGING

Part No.	Size
<b>FG001367</b>	4 Litres
<b>FG000920</b>	10 Litres
<b>FG000852</b>	20 Litres

## APPLICATION

Refer to the GUARDIAN Petrolatum System: Application Data Sheet.

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.