

- **GUARDIAN Petrolatum Mastic HT** is a key component of the **GUARDIAN Petrolatum System**.
- **GUARDIAN Petrolatum Mastic HT** is a blended reinforced petrolatum. Incorporating inert fillers, **GUARDIAN**
- **Petrolatum Mastic HT** also contains corrosion inhibitors and thermal extenders.
- **GUARDIAN Petrolatum Mastic HT** is inert, being stable in nature and maintaining its plasticity over a wide temperature range.
- **GUARDIAN Petrolatum Mastic HT** profiles crevices and sharp angles enabling **GUARDIAN Petrolatum Tape HT** to be applied without bridging or voiding.

PROPERTIES

Property	Test Method	Value
Flash Point		180°C
Specific Gravity	ASTM D70 @ 25°C (Mod)	1.1 (Average)
Drop Melting Point	ASTM D127 (Mod)	75°C
Petrolatum Content		75% Min. by Weight
Coverage*		1 to 2m ² /kg (Average)
*Note that coverage is determined by surface profile. Heavily pitted substrates will require more primer compared to a smooth surface substrate.		
Application Temperatures	-10 to +50°C	
Service Temperature	-10 to +75°C	
Service Life	20 Years +	
Shelf Life	20 Years +	

PACKAGING

Part No.	Weight	Unit	Carton Qty
PP04MP	4kg	Tub	2 Tubs/Carton
PP20MP	20kg	Drum	1 Drum

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.

BENEFITS

Isolates marine pile from the environment
Salt and seawater resistant
Contains water repellent and displacing agents

APPLICATION

Refer to the relevant **GUARDIAN System Application Data Sheet**