

- **GUARDIAN Bituwrap Primer** is a Bituminous Primer for use prior to the application of GUARDIAN Bituwrap 41HT or 1650 Tape Systems.
- **GUARDIAN Bituwrap Primer** can be applied by brush, roller or spray.
- **GUARDIAN Bituwrap Primer** is a fast drying solvent based Anti-Corrosion Bituminous Primer specially formulated to enable uniform adhesion of the nominated tape system to the cleaned pipeline substrate.

## ADVANTAGES

<b>Performance:</b>	
<b>Surface Preparation:</b>	AWWA C209-19
<b>High Tack:</b>	St2 (ISO 8501-1998) To promote the effective Bond between the Substrate and the Tape Compound.
<b>Versatility:</b>	Compound formulated for Maximum Adhesion for different applications and environments.

## PROPERTIES

<b>Specific Gravity</b>	0.91	(Average)
<b>Drying Time</b>	2-5 Minutes	(Average)
<b>Coverage</b>	7 m2/Litre	(Average)

## PACKAGING

PART NO.	SIZE
FG000619	5 Litre

## APPLICATION

<b>Application Temp:</b>	- 10 to + 50 °C
<b>Service Temp:</b>	- 10 to + 80 °C
<b>Service Life:</b>	+ 30 Years
<b>Shelf Life:</b>	3 Years from DOM

## FIRST AID

Wear suitable protective clothing when applying.  
Please refer to Material Safety Data Sheet for detailed safety precautions.

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.